Technical datasheet of CHP unit

KE-MTUNG 1000-BLE

	400 V / 50 Hz	Natural gas
Electrical power	kW	999
Total thermal output	kW	1114
Energy input	kW	2326
Fuel consumption	Nm^3/h	246,3
Electrical efficiency	%	42,9
Thermal efficiency with LT	%	51,0
Thermal efficiency without LT	%	47,9
Overall efficiency with LT	**%**	**93,9**

Engine: MTU Type: 8V4000L64FNER

No. of cylinders / configuration	-	8V
Engine speed	min^{-1}	1500
Bore / stroke / displacement	mm / mm / dm^3	170/210/38,1
Compression ratio	-	12,5
Engine power max.	kW	1026
Spark plugs type	-	M18
Lube oil consumption max.	dm^3/h	0,17
Lube oil filling quantity max.	dm^3	200

Alternator: Stamford Type:

Voltage / frequency	V/Hz	400/50
PF	-	0,8L / 0,95C
Alternator efficiency at rated power	%	97,4
Max. ambient temperature	°C	40

Energy balance

					CHP unit performance parameters at rated load
Load	%	**100**	**75**	**50**	**100**
ISO standard engine power	kW	1026	772	520	**1026**
Electrical power	kW	999	749	501	**999**
Engine cooling thermal output	kW	535	401	272	**535**
Exhaust gas thermal output (120 °C)	kW	516	428	345	**516**
Exhaust gas thermal output (80 °C)	kW	63	47	32	**63**
Thermal output mixture cooling - LT	kW	73	51	33	**73**
Total thermal output	kW	1114	876	649	**1114**
Radiation heat max.	kW	59	-	-	**59**
Energy input 1)	kW	2326	1789	1267	**2326**
Fuel consumption	Nm^3/h	246,3	189,4	134,2	**246,3**
Combustion air mass flow	kg/h	5074	3830	2595	**5074**
Exhaust gas mass flow, wet	kg/h	5244	3960	2688	**5244**
Exhaust temperature after turbocharger	°C	431	461	521	**431**
Alternator efficiency at PF=1	%	97,4	97,1	96,3	**97,4**
Electrical efficiency 1)	%	42,9	41,9	39,5	**42,9**
Thermal efficiency	%	47,9	49,0	51,2	**47,9**
Overall efficiency without LT	**%**	**90,8**	**90,9**	**90,7**	**90,8**

1) According to ISO 3046.

Fuel: Natural gas

Min. methane number	-	72
Lower calorific value	MJ/Nm^3	34
Gas pressure at gas regulation line inlet 1)	kPa	12÷25
Max. gas temperature	°C	30

1) The gas regulation line for MAN engines is standardly dimensioned at 4 ÷ 5 kPa.

Heating water circuit

Thermal output	kW	1114
Temperature gradient	°C / °C	90 / 70
Min. cooling medium volume flow	m^3/h	49,20
Max. allowable pressure loss 1)	kPa	50
Heat transfer medium	-	Treated water
Max. operating pressure	bar	6

1) Heating water circuit out of scope of supply of GENTEC CHP.

Technical datasheet of CHP unit KE-MTUNG 1000-BLE

LT mixture cooling circuit

Thermal output	kW	73
Temperature gradient	°C / °C	44,6 / 43
Cooling medium volume flow	m^3/h	41,70
Max. allowable pressure loss 1)	kPa	-
Heat transfer medium concentration - glycol / water	% vol./% vol.	40/60
Max. operating pressure	bar	6
Dry cooler acoustic sound pressure level at 10 m 2)	dB(A)	65
Max. ambient temperature	°C	35

1) Pipework between CHP unit and dry cooler.

2) The value of the sound pressure level is considered in free field.

Ventilation and combustion air

Fan air volume flow 1)	m^3/h	17900
Max. allowable pressure loss of air duct 2)	Pa	-
Max. inlet air temperature	°C	35

1) At temperature 35 °C and pressure 101,3 kPa.

2) Air ducts between CHP unit and air inlet/air outlet.

Exhaust gas system

Exhaust gas mass flow, wet	kg/h	5244
Exhaust gas temperature at CHP unit outlet	°C	80
Max. allowable pressure loss 1)	mbar	-
Silencer flanges 2)	-	-

1) Exhaust gas pipe between CHP unit and outlet excluding components at GENTEC CHP scope of supply.

2) According to EN 1092-1.

Emissions

CO	mg/Nm^3	<300
NO_x	mg/Nm^3	<250

Correlation 5% O_2.

Noise level

CHP unit design inside container 2)	dB(A)	70
Exhaust gas noise at 1 meter distance to silencer outlet 3)	dB(A)	80
Input/Output air ventilation 1)	dB(A)	80/80

All values of the sound pressure level is considered in free field.

1) Sound pressure level measured at 1 m distance from the CHP unit.

2) Sound pressure level measured at 10 m distance from the container.

3) On request, noise can be reduced by additional optimization of the standard silencer.

Dimensions and weight

Container dimensions L/W/H	mm	12200/2438/2900
Dry weight CHP unit design inside container	kg	23000

Technical datasheet of CHP unit

KE-MTUNG 1000-BLE

Standard conditions and tolerances

Atmospheric pressure	kPa	100
Air temperature	°C	25
Relative air humidity	%	30
Tolerance for the electrical power	%	±3
Tolerance for the usable thermal output	%	±8
Tolerance for the specific fuel consumption	%	+5

The energy balance parameters listed in this data sheet are related to the standard conditions.

Detailed technical specifications of components on demand.

Change of technical parameters and printing errors reserved.

Release date	Created	Revision	Project / Offer
2205	EB	0	