



400 V / 50 Hz

Propane

Electrical power	kW	71
Total thermal output	kW	117
Energy input	kW	210
Fuel consumption	Nm ³ /h	8,4
Electrical efficiency	%	34,0
Thermal efficiency with LT	%	59,0
Thermal efficiency without LT	%	55,7
Overall efficiency with LT	%	93,0

Engine: MAN Type: E0836 LE302

Alternator: Leroy-Somer

Type: LSA 44.3 L10

No. of cylinders / configuration	-	6 in line	Voltage / frequency	V/Hz	400/50
Engine speed	min ⁻¹	1500	PF	-	0,8L / 0,8C
Bore / stroke / displacement	mm / mm / dm ³	108/125/6,87	Alternator efficiency at rated power	%	95,1
Compression ratio	-	11	Max. ambient temperature	°C	40
Engine power max.	kW	75			
Spark plugs type	-	M14			
Lube oil consumption max.	kg/h	0,065			
Lube oil filling quantity max.	dm ³	34			

Energy balance

					CHP unit performance parameters at rated load
Load	%	100	75	50	100
ISO standard engine power	kW	75	-	-	75
Electrical power	kW	71	-	-	71
Engine cooling thermal output	kW	73	-	-	73
Exhaust gas thermal output (120 °C)	kW	44	-	-	44
Thermal output mixture cooling - HT	kW	-	-	-	-
Thermal output mixture cooling - LT	kW	7	-	-	7
Total thermal output	kW	117	-	-	117
Radiation heat max.	kW	3	-	-	3
Energy input 1)	kW	210	-	-	210
Fuel consumption	Nm ³ /h	8,4	-	-	8,4
Combustion air mass flow	kg/h	424	-	-	424
Exhaust gas mass flow, wet	kg/h	441	-	-	441
Exhaust temperature after turbocharger	°C	450	-	-	450
Alternator efficiency at PF=1	%	95,1	-	-	95,1
Electrical efficiency 1)	%	34,0	-	-	34,0
Thermal efficiency	%	55,7	-	-	55,7
Overall efficiency without LT	%	89,7	-	-	89,7

1) According to ISO 3046.

Fuel: Propane

Min. methane number	-	30
Lower calorific value	MJ/Nm ³	90
Gas pressure at gas regulation line inlet 1)	kPa	1,5÷10
Max. gas temperature	°C	30

1) The gas regulation line for MAN engines is standardly dimensioned at 4 ÷ 5 kPa.

Heating water circuit

Thermal output	kW	117
Temperature gradient	°C / °C	90 / 70
Min. cooling medium volume flow	m ³ /h	5,17
Pressure loss of heating circuit 1)	bar	0,12
Heat transfer medium	-	Treated water
Max. operating pressure	bar	6

1) Pressure loss of all heating water circuit components at GENTEC CHP scope of supply.

LT mixture cooling circuit

Thermal output	kW	7
Temperature gradient	°C / °C	44 / 40
Cooling medium volume flow	m ³ /h	1,64
Max. allowable pressure loss 1)	kPa	20
Heat transfer medium concentration - glycol / water	% vol./% vol.	40/60
Max. operating pressure	bar	3
Dry cooler acoustic sound pressure level at 10 m 2)	dB(A)	65
Max. ambient temperature	°C	35

1) Pipework between CHP unit and dry cooler.

2) The value of the sound pressure level is considered in free field.

Ventilation and combustion air

Fan air volume flow 1)	m ³ /h	1800
Max. allowable pressure loss of air duct 2)	Pa	50
Max. inlet air temperature	°C	35

1) At temperature 35 °C and pressure 101,3 kPa.

2) Air ducts between CHP unit and air inlet/air outlet.

Exhaust gas system

Exhaust gas mass flow, wet	kg/h	441
Exhaust gas temperature at CHP unit outlet	°C	120
Max. allowable pressure loss 1)	mbar	6
Silencer flanges 2)	-	DN125-PN10

1) Exhaust gas pipe between CHP unit and outlet excluding components at GENTEC CHP scope of supply.

2) According to EN 1092-1.

Emissions

CO	mg/Nm ³	<650
NO _x	mg/Nm ³	<500

Correlation 5% O₂.

Noise level

CHP unit design without canopy 1)	dB(A)	83,1
CHP unit design with canopy 1)	dB(A)	74
Exhaust gas noise at 1 meter distance to silencer outlet 3)	dB(A)	80
Input/Output air ventilation 1)	dB(A)	80/80

All values of the sound pressure level is considered in free field.

1) Sound pressure level measured at 1 m distance from the CHP unit.

2) Sound pressure level measured at 10 m distance from the container.

3) On request, noise can be reduced by additional optimization of the standard silencer.

Dimensions and weight

Canopy dimensions L/W/H	mm	3535/1308/1805
Dry weight of CHP unit design with canopy	kg	3800

Standard conditions and tolerances

Atmospheric pressure	kPa	100
Air temperature	°C	25
Relative air humidity	%	30
Tolerance for the electrical power	%	±3
Tolerance for the usable thermal output	%	±7
Tolerance for the specific fuel consumption	%	+8

The energy balance parameters listed in this data sheet are related to the standard conditions.

Detailed technical specifications of components on demand.

Change of technical parameters and printing errors reserved.

Release date	Created	Revision	Project / Offer
2212	EB	0	