



	400 V / 50 Hz	Propane
Electrical power	kW	144
Total thermal output	kW	222
Energy input	kW	409
Fuel consumption	Nm ³ /h	16,4
Electrical efficiency	%	35,1
Thermal efficiency with LT	%	57,9
Thermal efficiency without LT	%	54,3
Overall efficiency with LT	%	93,0

Engine: MAN Type: E2876 LE302

Alternator: Leroy-Somer

Type: LSA 46.3 L10

No. of cylinders / configuration	-	6 in line	Voltage / frequency	V/Hz	400/50
Engine speed	min ⁻¹	1500	PF	-	0,8L / 0,8C
Bore / stroke / displacement	mm / mm / dm ³	128/166/12,82	Alternator efficiency at rated power	%	95,8
Compression ratio	-	11	Max. ambient temperature	°C	40
Engine power max.	kW	150			
Spark plugs type	-	M14			
Lube oil consumption max.	kg/h	0,15			
Lube oil filling quantity max.	dm ³	70			

Energy balance

					CHP unit performance parameters at rated load
Load	%	100	75	50	100
ISO standard engine power	kW	150	-	-	150
Electrical power	kW	144	-	-	144
Engine cooling thermal output	kW	91	-	-	91
Exhaust gas thermal output (120 °C)	kW	122	-	-	122
Thermal output mixture cooling - HT	kW	9	-	-	9
Thermal output mixture cooling - LT	kW	15	-	-	15
Total thermal output	kW	222	-	-	222
Radiation heat max.	kW	13	-	-	13
Energy input 1)	kW	409	-	-	409
Fuel consumption	Nm ³ /h	16,4	-	-	16,4
Combustion air mass flow	kg/h	841	-	-	841
Exhaust gas mass flow, wet	kg/h	873	-	-	873
Exhaust temperature after turbocharger	°C	550	-	-	550
Alternator efficiency at PF=1	%	95,8	-	-	95,8
Electrical efficiency 1)	%	35,1	-	-	35,1
Thermal efficiency	%	54,3	-	-	54,3
Overall efficiency without LT	%	89,4	-	-	89,4

1) According to ISO 3046.

Fuel: Propane

Min. methane number	-	30
Lower calorific value	MJ/Nm ³	90
Gas pressure at gas regulation line inlet 1)	kPa	1,5÷10
Max. gas temperature	°C	30

1) The gas regulation line for MAN engines is standardly dimensioned at 4 ÷ 5 kPa.

Heating water circuit

Thermal output	kW	222
Temperature gradient	°C / °C	90 / 70
Min. cooling medium volume flow	m ³ /h	9,80
Pressure loss of heating circuit 1)	bar	0,12
Heat transfer medium	-	Treated water
Max. operating pressure	bar	6

1) Pressure loss of all heating water circuit components at GENTEC CHP scope of supply.

LT mixture cooling circuit

Thermal output	kW	15
Temperature gradient	°C / °C	44 / 40
Cooling medium volume flow	m ³ /h	3,51
Max. allowable pressure loss 1)	kPa	20
Heat transfer medium concentration - glycol / water	% vol./% vol.	40/60
Max. operating pressure	bar	3
Dry cooler acoustic sound pressure level at 10 m 2)	dB(A)	65
Max. ambient temperature	°C	35

1) Pipework between CHP unit and dry cooler.

2) The value of the sound pressure level is considered in free field.

Ventilation and combustion air

Fan air volume flow 1)	m ³ /h	4800
Max. allowable pressure loss of air duct 2)	Pa	50
Max. inlet air temperature	°C	35

1) At temperature 35 °C and pressure 101,3 kPa.

2) Air ducts between CHP unit and air inlet/air outlet.

Exhaust gas system

Exhaust gas mass flow, wet	kg/h	873
Exhaust gas temperature at CHP unit outlet	°C	120
Max. allowable pressure loss 1)	mbar	6
Silencer flanges 2)	-	DN200-PN10

1) Exhaust gas pipe between CHP unit and outlet excluding components at GENTEC CHP scope of supply.

2) According to EN 1092-1.

Emissions

CO	mg/Nm ³	<650
NO _x	mg/Nm ³	<500

Correlation 5% O₂.

Noise level

CHP unit design without canopy 1)	dB(A)	88,1
CHP unit design with canopy 1)	dB(A)	74
Exhaust gas noise at 1 meter distance to silencer outlet 3)	dB(A)	80
Input/Output air ventilation 1)	dB(A)	80/80

All values of the sound pressure level is considered in free field.

1) Sound pressure level measured at 1 m distance from the CHP unit.

2) Sound pressure level measured at 10 m distance from the container.

3) On request, noise can be reduced by additional optimization of the standard silencer.

Dimensions and weight

Canopy dimensions L/W/H	mm	3945/1708/2180
Dry weight of CHP unit design with canopy	kg	6000

Standard conditions and tolerances

Atmospheric pressure	kPa	100
Air temperature	°C	25
Relative air humidity	%	30
Tolerance for the electrical power	%	±3
Tolerance for the usable thermal output	%	±7
Tolerance for the specific fuel consumption	%	+8

The energy balance parameters listed in this data sheet are related to the standard conditions.

Detailed technical specifications of components on demand.

Change of technical parameters and printing errors reserved.

Release date	Created	Revision	Project / Offer
12.06.2023	EB	0	