Technical datasheet of CHP unit

KE-MBG 300LE252-AS

400 V / 50 Hz		Biogas
Electrical power	kW	308
Total thermal output	kW	362
Energy input	kW	790
Fuel consumption	Nm^3/h	131,7
Electrical efficiency	%	39,0
Thermal efficiency with LT	%	47,6
Thermal efficiency without LT	%	45,8
Overall efficiency with LT	**%**	**86,6**

Engine: MAN Type: E3268 LE252

No. of cylinders / configuration	-	8V
Engine speed	min^{-1}	1500
Bore / stroke / displacement	mm / mm / dm^3	132/157/17,19
Compression ratio	-	12
Engine power max.	kW	320
Spark plugs type	-	M18
Lube oil consumption max.	kg/h	0,14
Lube oil filling quantity max.	dm^3	95

Alternator: Leroy-Somer Type: LSA 47.3 S4

Voltage / frequency	V/Hz	400/50
PF	-	0,8L / 0,8C
Alternator efficiency at rated power	%	96,3
Max. ambient temperature	°C	40

Energy balance

					CHP unit performance parameters at rated load
Load	%	**100**	**75**	**50**	**100**
ISO standard engine power	kW	320	240	160	**320**
Electrical power	kW	308	232	154	**308**
Engine cooling thermal output	kW	173	153	126	**173**
Exhaust gas thermal output (180 °C)	kW	165	132	92	**165**
Thermal output mixture cooling - HT	kW	24	7	0	**24**
Thermal output mixture cooling - LT	kW	14	10	4	**14**
Total thermal output	kW	362	292	218	**362**
Radiation heat max.	kW	13	12	5	**13**
Energy input 1)	kW	790	617	431	**790**
Fuel consumption	Nm^3/h	131,7	102,8	71,8	**131,7**
Combustion air mass flow	kg/h	1502	1150	782	**1502**
Exhaust gas mass flow, wet	kg/h	1663	1275	870	**1663**
Exhaust temperature after turbocharger	°C	473	486	493	**473**
Alternator efficiency at PF=1	%	96,3	96,5	96,3	**96,3**
Electrical efficiency 1)	%	39,0	37,5	35,7	**39,0**
Thermal efficiency	%	45,8	47,3	50,5	**45,8**
Overall efficiency without LT	**%**	**84,8**	**84,8**	**86,2**	**84,8**

1) According to ISO 3046.

Fuel: Biogas

Min. methane number	-	100
Lower calorific value	MJ/Nm^3	21,6
Biogas composition $CH_4/C0_2$	% vol./% vol.	60/40
Gas pressure at gas regulation line inlet 1)	kPa	4÷10
Max. gas temperature	°C	30

1) The gas regulation line for MAN engines is standardly dimensioned at 4 ÷ 5 kPa.

Heating water circuit

Thermal output	kW	362
Temperature gradient	°C / °C	90 / 70
Min. cooling medium volume flow	m^3/h	15,98
Pressure loss of heating circuit 1)	bar	0,12
Heat transfer medium	-	Treated water
Max. operating pressure	bar	6

1) Pressure loss of all heating water circuit components at GENTEC CHP scope of supply.

LT mixture cooling circuit

Thermal output	kW	14
Temperature gradient	°C / °C	46 / 42
Cooling medium volume flow	m^3/h	3,27
Max. allowable pressure loss 1)	kPa	20
Heat transfer medium concentration - glycol / water	% vol./% vol.	40/60
Max. operating pressure	bar	3
Dry cooler acoustic sound pressure level at 10 m 2)	dB(A)	65
Max. ambient temperature	°C	35

1) Pipework between CHP unit and dry cooler.

2) The value of the sound pressure level is considered in free field.

Emergency cooler

Thermal output	kW	362
Heat transfer medium	-	Ethylene glycol/Water-40/60
Max. allowable pressure loss 1)	kPa	15
Dry cooler acoustic sound pressure level at 10 m 2)	dB(A)	65
Max. ambient temperature	°C	35

1) Pipework between CHP unit and dry cooler.

2) The value of the sound pressure level is considered in free field

Ventilation and combustion air

Fan air volume flow 1)	m^3/h	6600
Max. allowable pressure loss of air duct 2)	Pa	50
Max. inlet air temperature	°C	35

1) At temperature 35 °C and pressure 101,3 kPa.

2) Air ducts between CHP unit and air inlet/air outlet.

Exhaust gas system

Exhaust gas mass flow, wet	kg/h	1663
Exhaust gas temperature at CHP unit outlet	°C	180
Max. allowable pressure loss 1)	mbar	6
Silencer flanges 2)	-	DN250-PN10

1) Exhaust gas pipe between CHP unit and outlet excluding components at GENTEC CHP scope of supply.

2) According to EN 1092-1.

Emissions

CO	mg/Nm^3	<650
NO_x	mg/Nm^3	<500

Correlation 5% O_2.

Noise level

CHP unit design without canopy 1)	dB(A)	90
CHP unit design with canopy 1)	dB(A)	74
Exhaust gas noise at 1 meter distance to silencer outlet 3	dB(A)	80
Input/Output air ventilation 1)	dB(A)	80/80

All values of the sound pressure level is considered in free field.

1) Sound pressure level measured at 1 m distance from the CHP unit.

2) Sound pressure level measured at 10 m distance from the container.

3) On request, noise can be reduced by additional optimization of the standard silencer.

Dimensions and weight

Canopy dimensions L/W/H	mm	4500/1950/2200
Dry weight of CHP unit design with canopy	kg	7300

Standard conditions and tolerances

Atmospheric pressure	kPa	100
Air temperature	°C	25
Relative air humidity	%	30
Tolerance for the electrical power	%	±3
Tolerance for the usable thermal output	%	±7
Tolerance for the specific fuel consumption	%	+5

The energy balance parameters listed in this data sheet are related to the standard conditions.

Detailed technical specifications of components on demand.

Change of technical parameters and printing errors reserved.

Release date	Created	Revision	Project / Offer
2302	MO	0	